

Introduction To Standard ML



CS251 Programming Languages Fall 2016, Lyn Turbak

Department of Computer Science
Wellesley College

The ML Programming Language

ML (Meta Language) was developed by Robin Milner in 1975 for specifying theorem provers. It since has evolved into a general purpose programming language.

Important features of ML:

- **static typing**: catches type errors at compile-time.
- **type reconstruction**: infers types so programmers don't have to write them explicitly
- **polymorphism**: functions and values can be parameterized over types (think Java generics, but much better).
- **function-oriented (functional)**: encourages a composition-based style of programming and first-class functions
- **sum-of-products datatypes with pattern-matching**: simplifies the manipulation of tree-structured data

These features make ML an excellent language for mathematical calculation, data structure implementation, and programming language implementation.

Introduction to Standard ML 2

ML Dialects

There are several different dialects of ML. The two we use at Wellesley are:

- **Standard ML (SML)**: Version developed at AT&T Bell Labs. We'll use this in CS251. The particular implementation we'll use is Standard ML of New Jersey (SMLNJ):

<http://www.smlnj.org/>

- **Objective CAML**: Version developed at INRIA (France). We have sometimes used this in other Wellesley courses.

These dialects differ in minor ways (e.g., syntactic conventions, library functions). See the following for a comparison:

<http://www.mpi-sws.mpg.de/~rossberg/sml-vs-ocaml.html>

Introduction to Standard ML 3

For now: run sml on cs.wellesley.edu

- Lyn is still working out details with SML on different versions of Ben's wx Virtual Machine appliance (which is used in CS240). I'll email the class when I have this figured out.
- So for now, we'll be experimenting with SML on the CS server = cs.wellesley.edu = tempest.
- Begin by connecting to your CS server account via ssh.
 - On a Mac, you can do this in your terminal window.
 - On a Windows PC, you'll need to use a terminal emulator like putty

```
[fturbak@Franklyns-MBP ~]$ ssh gdome@cs.wellesley.edu
gdome@cs.wellesley.edu's password:
Last login: Wed Oct 26 15:28:23 2016 from 149.130.142.18
```

```
[gdome@tempest ~] which sml
/usr/local/smlnj/bin/sml
```

```
[gdome@tempest ~] sml
Standard ML of New Jersey v110.78 [built: Wed Jan 14 12:52:09 2015]
```

```
- 1 + 2;
val it = 3
```

Introduction to Standard ML 4

Learning SML by Interactive Examples

Try out these examples. (Note: many answers are missing in these slides so you can predict them. See the solns slides for answers.)

```
[gdome@tempest ~] sml
Standard ML of New Jersey v110.78 [built: Wed Jan 14 12:52:09 2015]

- 1 + 2;
val it =

- 3+4;
val it =

- 5+6
= ;
val it =

- 7
= +
= 8;
val it =
```

Naming Values

```
- val a = 2 + 3;
val a = : int

- a * a;
val it = : int

- it + a;
val it = : int
```

Negative Quirks

```
- 2 - 5;
val it = ~3 : int

- -17;
stdIn:60.1 Error: expression or pattern begins with infix
identifier "-"
stdIn:60.1-60.4 Error: operator and operand don't agree
[literal]
  operator domain: 'Z * 'Z
  operand:         int
  in expression:
    - 17

- ~17;
val it = ~17 : int

- 3 * ~1;
val it = ~3 : int
```

Division Quirks

```
- 7 / 2;
stdIn:1.1-1.6 Error: operator and operand don't agree
[literal]
  operator domain: real * real
  operand:         int * int
  in expression:
    7 / 2

- 7.0 / 2.0;
val it = 3.5 : real

- 7 div 2; (* integer division *)
val it = 3 : int

(* For a description of all top-level operators, see:
http://www.standardml.org/Basis/top-level-chapter.html *)
```

Simple Functions

```
- val inc = fn x => x + 1;
val inc = fn : int -> int (* SML figures out type! *)

- inc a;
val it =      : int

- fun dbl y = y * 2;
  (* Syntactic sugar for val dbl = fn y => y * 2 *)
val dbl = fn : int -> int

- dbl 5;
val it =      : int

- (fn x => x * 3) 10; (* Don't need to name function to use it *)
val it =      : int
```

When Parentheses Matter

```
- dbl(5); (* parens are optional here *)
val it = 10 : int

- (dbl 5); (* parens are optional here *)
val it = 10 : int

- inc (dbl 5); (* parens for argument subexpressions are required! *)
val it = 11 : int

- (inc dbl) 5;
stdIn:1.2-2.2 Error: operator and operand don't agree [tycon mismatch]
operator domain: int
operand:         int -> int
in expression:
  inc dbl

- inc dbl 5; (* default left associativity for application *)
stdIn:22.1-22.10 Error: operator and operand don't agree [tycon
mismatch]
operator domain: int
operand:         int -> int
in expression:
  inc dbl
```

Function Composition

```
- (inc o dbl) 10; (* SML builtin infix function composition *)
val it =      : int

- (dbl o inc) 10;
val it =      : int

- fun id x = x; (* we can define our own identity fcn *)
val id = fn : 'a -> 'a (* polymorphic type; compare to
  Java's public static <T> T id (T x) {return x;} *)

- (inc o id) 10;
val it =      : int

- (id o dbl) 10;
val it =      : int

- (inc o inc o inc o inc) 10;
val it =      : int
```

Functions as Arguments

```
- fun app5 f = f 5;
val app5 = fn : (int -> 'a) -> 'a

- app5 inc;
val it =      : int

- app5 dbl;
val it =      : int

- app5 (fn z => z - 2);
val it =      : int
```

We'll see later that functions can also be returned as results from other functions and stored in data structures, so functions are first-class in SML just as in Racket.

Scope of Top-Level Names

```
- val b = a * 2; (* recall a is 5 from before *)
val b =      : int

- fun adda x = x + a; (* a is still 5 from before *)
val adda = fn : int -> int

- adda 7;
val it =      : int

- adda b;
val it =      : int

- val a = 42; (* this is a different a from the previous one *)
val a =      : int

- b; (* ML values are immutable; nothing can change b's value *)
val it =      : int

- adda 7;
val it =      : int (* still uses the a where adda was defined *)
```

Introduction to Standard ML 13

Booleans

```
- 1 = 1;
val it =      : bool

- 1 > 2;
val it =      : bool

- (1 = 1) andalso (1 > 2);
val it =      : bool

- (1 = 1) orelse (1 = 2);
val it =      : bool

- (3 = 4) andalso (5 = (6 div 0)); (* short-circuit evaluation *)
val it =      : bool

- fun isEven n = (n mod 2) = 0;
val isEven = fn : int -> bool (* SML figures out type! *)

- isEven 17;
val it =      : bool

- isEven 6;
val it =      : bool
```

Introduction to Standard ML 14

Conditionals

```
- fun f n = if n > 10 then 2 * n else n * n;
val f = fn : int -> int

- f 20;
val it =      : int

- f 5;
val it =      : int
```

Introduction to Standard ML 15

Recursion

```
- fun fact n =
=   if n = 0 then
=     1
=   else
=     n * (fact (n - 1)); (* fun names have recursive scope *)
val fact = fn : int -> int
    (* simpler than Java definition b/c no explicit types! *)

- fact 5;
val it =      : int

- fact 12;
val it =      : int

- fact 13;
uncaught exception Overflow [overflow]
  raised at: <file stdIn>
    (* SML ints have limited size ☹ *)
```

Introduction to Standard ML 16

Local Naming via `let`

`let` is used to define local names. Any such names “shadow” existing definitions from the surrounding scope.

```
- let val a = 27 (* 1st let binding *)
=     val b = 3  (* 2nd binding *)
=     fun fact x = x + 2 (* 3rd binding *)
=     in fact (a div b) (* let body *)
= end; (* end terminates the let *)
val it =      : int
```

`let`-bound names are only visible in the body of the `let`.

```
- fact (a div b); (* these are global names *)
val it =      : int
```

Introduction to Standard ML 17

Make and populate a `~/cs251/sml` directory

```
[gdome@tempest ~] pwd
~/students/gdome

[gdome@tempest ~] mkdir cs251

[gdome@tempest ~] cd cs251

[gdome@tempest cs251] mkdir sml

[gdome@tempest cs251] cd sml

[gdome@tempest sml] pwd
~/students/gdome/cs251/sml

[gdome@tempest sml] cp ~/cs251/download/sml/* .

[gdome@tempest sml] ls
listfuns.sml load-fact.sml mydefns.sml
step-more.sml step.sml test-fact.sml
```

Introduction to Standard ML 18

Easier to Put Your Code in a File

```
(* This is the contents of the file
   ~/gdome/cs251/sml/mydefns.sml.
   (* By the way, comments nest properly in SML! *)
   It defines integers a and b and the fact function. *)

val a = 2 + 3

val b = 2 * a

fun fact n = (* a recursive factorial function *)
  if n = 0 then
    1
  else
    n * (fact (n - 1))
```

- File is a sequence of value/function definitions.
- Definitions are **not** followed by semi-colons in files!
- There are **no equal signs** for multiple-line definitions.

Introduction to Standard ML 19

Using Code From a File

```
- Posix.FileSys.getcwd(); (* current working directory *)
val it = "/students/gdome" : string

- Posix.FileSys.chdir("/students/gdome/cs251/sml");
  (* change working directory *)
val it = () : unit

- Posix.FileSys.getcwd();
val it = "/students/gdome/cs251/sml" : string

- use "mydefns.sml"; (* load defns from file as if *)
[opening mydefns.sml] (* they were typed manually *)
val a = 5 : int
val b = 10 : int
val fact = fn : int -> int
val it = () : unit

- fact a
val it = 120 : int
```

Introduction to Standard ML 20

Another File Example

```
(* This is the contents of the file test-fact.sml *)
val fact_3 = fact 3
val fact_a = fact a
```

```
- use "test-fact.sml";
[opening test-fact.sml]
val fact_3 = 6 : int
val fact_a = 120 : int
val it = () : unit
```

Nested File Uses

```
(* The contents of the file load-fact.sml *)
use "mydefns.sml"; (* semi-colons are required here *)
use "test-fact.sml";
```

```
- use "load-fact.sml";
[opening load-fact.sml]
[opening mydefns.sml]
val a = 5 : int
val b = 10 : int
val fact = fn : int -> int
val it = () : unit
[opening test-fact.sml]
val fact_3 = 6 : int
val fact_a = 120 : int
val it = () : unit
val it = () : unit
```

Tuples

```
- val tpl = (1 + 2, 3 < 4, 5 * 6, 7 = 8);
val tpl = ( , , , ) : int * bool * int * bool
```

```
- #1 tpl;
val it = : int
```

```
- #2 tpl;
val it = : bool
```

```
(* In practice, always use pattern matching (below)
rather than #1, #2, etc. *)
```

```
- ((#1 tpl) + (#3 tpl), (#2 tpl) orelse (#4 tpl));
val it = ( , ) : int * bool
```

```
(* Can "deconstruct" tuples via pattern matching *)
```

```
- let val (i1, b1, i2, b2) = tpl
= in (i1 + i2, b1 orelse b2)
= end;
val it = ( , ) : int * bool
```

Strings

```
- "foobar";
val it = : string
```

```
- "foo" ^ "bar" ^ "baz";
val it = : string
```

```
- print ("baz" ^ "quux");
bazquuxval it = () : unit
```

```
- print ("baz" ^ "quux\n"); (* parens are essential here! *)
bazquux
val it = () : unit
```

```
- print "baz" ^ "quux\n";
stdIn:1.1-1.23 Error: operator and operand don't agree
[tycon mismatch]
operator domain: string * string
operand:          unit * string
in expression:
  print "baz" ^ "quux\n"
```

Other String Operations

```
- String.size ("foo" ^ "bar");
val it =      : int

- String.substring ("abcdefg", 2, 3); (* string, start index, len *)
val it =      : string

("bar" < "foo", "bar" <= "foo", "bar" = "foo", "bar" > "foo");
val it = (    ,    ,    ,    ) : bool * bool * bool * bool

-(String.compare("bar", "foo"), String.compare("foo", "foo"),
 = String.compare("foo", "bar"));
val it = (    ,    ,    ) : order * order * order

- String.size;
val it = fn : string -> int

- String.substring;
val it = fn : string * int * int -> string

- String.compare;
val it = fn : string * string -> order

(* An API for all SMLNJ String operations can be found at:
http://www.standardml.org/Basis/string.html *)
```

Introduction to Standard ML 25

Characters

```
- #"a";
val it = #"a" : char

- String.sub ("foobar",0);
val it =      : char

- String.sub ("foobar",5);
val it =      : char

- String.sub ("foobar",6);
uncaught exception Subscript [subscript out of bounds]
  raised at: stdIn:17.1-17.11

- String.str #"a"; (* convert a char to a string *)
val it = "a" : string

- (String.str (String.sub ("ABCD",2))) ^ "S"
 = ^ (Int.toString (112 + 123));
val it =      : string

- (1+2, 3=4, "foo" ^ "bar", String.sub("baz",2));
val it = (    ,    ,    ,    ) : int * bool * string * char
```

Introduction to Standard ML 26

Pattern-matching Function Arguments

```
- fun swap (x,y) = (y, x);
val swap = fn : 'a * 'b -> 'b * 'a (* infers polymorphic type *)

- swap (1+2, 3=4);
val it =      : bool * int

- swap (swap (1+2, 3=4));
val it =      : int * bool

- swap ((1+2, 3=4), ("foo" ^ "bar", String.sub("baz",2)));
val it =      : (string * char) * (int *
bool)
```

Introduction to Standard ML 27

How to Pass Multiple Arguments

```
- fun avg1 (x, y) = (x + y) div 2; (* Approach 1: use pairs *)
val avg1 = fn : int * int -> int

- avg1 (10,20);
val it =      : int

- fun avg2 x = (fn y => (x + y) div 2); (* Approach 2: currying *)
val avg2 = fn : int -> int -> int

- avg2 10 20;
val it =      : int

- fun avg3 x y = (x + y) div 2; (* Syntactic sugar for currying *)
val avg3 = fn : int -> int -> int

- avg3 10 20;
val it =      : int

- app5 (avg3 15);
val it =      : int

- app5 (fn i => avg1(15,i));
val it =      : int
```

Introduction to Standard ML 28

Iterating via Tail Recursion

```
(* This is the contents of the file step.sml *)
```

```
fun step (a,b) = (a+b, a*b)

fun stepUntil ((a,b), limit) = (* no looping constructs in ML; *)
  if a >= limit then          (* use tail recursion instead! *)
    (a,b)
  else
    stepUntil (step(a,b), limit)
```

```
- use ("step.sml");
[opening step.sml]
val step = fn : int * int -> int * int
val stepUntil = fn : (int * int) * int -> int * int
val it = () : unit

- step (1,2);
val it = (3,2) : int * int

- step (step (1,2));
val it = (5,6) : int * int

- let val (x,y) = step (step (1,2)) in x*y end;
val it = 30 : int

- stepUntil ((1,2), 100);
val it = (371,13530) : int * int
```

Introduction to Standard ML 29

Adding print statements

```
(* This is the contents of the file step-more.sml *)
```

```
fun printPair (a,b) =
  print ("(" ^ (Int.toString a) ^ ", "
    ^ (Int.toString b) ^ ")\n")

fun stepUntilPrint ((a,b), limit) =
  if a >= limit then
    (a,b)
  else
    (printPair (a,b); (* here, semicolon sequences expressions *)
     stepUntilPrint (step(a,b), limit))
```

```
- use ("step-more.sml");
[opening step-more.sml]
val printPair = fn : int * int -> unit
val stepUntilPrint = fn : (int * int) * int -> int * int
val it = () : unit

- stepUntilPrint ((1,2),100);
(1,2)
(3,2)
(5,6)
(11,30)
(41,330)
val it = (371,13530) : int * int
```

Introduction to Standard ML 30

How to exit SML interpreter?

```
[gdome@tempest ~] sml
Standard ML of New Jersey v110.78
[built: Wed Jan 14 12:52:09 2015]
```

```
- 1 + 2;
val it = 3 : int
```

```
-  Type Control-d at the SML prompt
```

```
[gdome@tempest ~]
```

Introduction to Standard ML 31