

Sum-of-Product Datatypes in SML




CS251 Programming Languages
Spring 2016, Lyn Turbak

Department of Computer Science
Wellesley College

Motivating example: geometric figures

Suppose we want to represent geometric figures like circles, rectangles, and triangles so that we can do things like calculate their perimeters, scale them, etc. (Don't worry about drawing them!)




These are so-called **sum of products** data:

- Circle, Rect, and Tri are tags that distinguish which one in a sum
- The numeric children of each tag are the product associated with that tag.

How would you do this in Java? In Python?

Sum-of-Product Datatypes in SML 14-2

SML's datatype for Sum-of-Product types



```
datatype figure =  
  Circ of real (* radius *)  
| Rect of real * real (* width, height *)  
| Tri of real * real * real (* side1, side2, side3 *)  
  
val figs = [Circ 1.0, Rect (2.0,3.0), Tri (4.0,5.0,6.0)]  
(* List of sample figures *)  
  
val circs = map Circ [7.0, 8.0, 9.0]  
(* List of three circles *)
```

Sum-of-Product Datatypes in SML 14-3

Functions on datatype via pattern matching

```
(* Return perimeter of figure *)  
fun perim (Circ r) = 2.0 * Math.pi * r  
| perim (Rect(w,h)) = 2.0 * (w + h)  
| perim (Tri(s1,s2,s3)) = s1 + s2 + s3  
  
(* Scale figure by factor n *)  
fun scale n (Circ r) = Circ (n * r)  
| scale n (Rect(w,h)) = Rect (n*w, n*h)  
| scale n (Tri(s1,s2,s3)) = Tri (n*s1, n*s2, n*s3)
```

```
- val perims = map perim figs  
val perims = [6.28318530718,10.0,15.0] : real list  
  
- val scaledFigs = map (scale 3.0) figs  
val scaledFigs = [Circ 3.0,Rect (6.0,9.0),  
                  Tri (12.0,15.0,18.0)] : figure list
```

Sum-of-Product Datatypes in SML 14-4

Options

SML has a built-in option datatype defined as follows:

```
datatype 'a option = NONE | SOME of 'a
```

```
- NONE
val it = NONE : 'a option

- SOME 3;
val it = SOME 3 : int option

- SOME true;
val it = SOME true : bool option
```

Sum-of-Product Datatypes in SML 14-5

Sample Use of Options

```
- fun into_100 n = if (n = 0) then NONE else SOME (100 div n);
val into_100 = fn : int -> int option

- List.map into_100 [5, 3, 0, 10];
val it = [SOME 20,SOME 33,NONE,SOME 10] : int option list

- fun addOptions (SOME x) (SOME y) = SOME (x + y)
=   | addOptions (SOME x) NONE = NONE
=   | addOptions NONE (SOME y) = NONE
=   | addOptions NONE NONE = NONE;
val addOptions = fn : int option -> int option -> int option

- addOptions (into_100 5) (into_100 10);
val it = SOME 30 : int option

- addOptions (into_100 5) (into_100 0);
val it = NONE : int option
```

Sum-of-Product Datatypes in SML 14-6

Options and List.find

```
(* List.find : ('a -> bool) -> 'a list -> 'a option *)
- List.find (fn y => (y mod 2) = 0) [5,8,4,1];
val it = SOME 8 : int option

- List.find (fn z => z < 0) [5,8,4,1];
val it = NONE : int option
```

Sum-of-Product Datatypes in SML 14-7

Thinking about options

What problem does option solve?

How is the problem solved in other languages?

Sum-of-Product Datatypes in SML 14-8

Creating our own list datatype

```
datatype 'a mylist = Nil | Cons of 'a * 'a mylist

val ints = Cons(1, Cons(2, Cons(3, Nil))) (* : int mylist *)

val strings = Cons("foo", Cons("bar", Cons("baz", Nil)))
(* : strings mylist *)




fun myMap f Nil = Nil
  | myMap f (Cons(x,xs)) = Cons(f x, myMap f xs)
(* : ('a -> 'b) -> 'a mylist -> 'b mylist *)

val incNums = myMap (fn x => x + 1) ints
(* val incNums= Cons (2,Cons (3,Cons (4,Nil))) : int mylistval *)

val myStrings = myMap (fn s => "my " ^ s) strings
(* val myStrings = Cons ("my foo", Cons ("my bar", Cons ("my
baz",Nil))): string mylist *)
```


Sum-of-Product Datatypes in SML 14-9

Binary Trees



Sum-of-Product Datatypes in SML 14-10

SML bintree datatype for Binary Trees




```
datatype 'a bintree =
  Leaf
  | Node of 'a bintree * 'a * 'a bintree
  (* left subtree, value, right subtree *)
```

```
val int_tree= Node(Node(Leaf,2,Leaf),
  4,
  Node(Node(Leaf, 1, Node(Leaf, 5, Leaf)),
    6,
    Node(Leaf, 3, Leaf)))
```

Sum-of-Product Datatypes in SML 14-11


bintree can have any type of element



```
val string_tree = Node(Node (Leaf,"like",Leaf),
  "green",
  Node (Node (Leaf,"and",Leaf),
    "eggs",
    Node (Leaf,"ham",Leaf)))
```

Sum-of-Product Datatypes in SML 14-12

Counting nodes in a binary tree




```
fun num_nodes Leaf = 0
| num_nodes (Node(l,v,r)) = 1 + (num_nodes l) + (num_nodes r)
```

```
~ num_nodes int_tree;
val it = 6 : int

- num_nodes string_tree;
val it = 5 : int
```

Sum-of-Product Datatypes in SML 14-13

Your turn: height




```
(* val height = fn : 'a bintree -> int *)
(* Returns the height of a binary tree. *)
(* Note: Int.max returns the max of two ints *)
```

```
~ height int_tree;
val it = 4 : int

- height string_tree;
val it = 3 : int
```

Sum-of-Product Datatypes in SML 14-14

Your turn: sum_nodes




```
(* val sum_nodes = fn : int bintree -> int *)
(* Returns the sum of node values in binary tree of ints *)
```

```
~ sum_nodes int_tree;
val it = 21 : int
```

Sum-of-Product Datatypes in SML 14-15

Your turn: inlist




```
(* val inlist = fn : 'a bintree -> 'a list *)
(* Returns a list of the node values in in-order *)
```

```
- inlist int_tree;
val it = [2,4,1,5,6,3] : int list

- inlist string_tree;
- val it = ["like","green","eggs","and","ham"] : string list
```

Sum-of-Product Datatypes in SML 14-16

Your turn: map_tree




```
(* val map_tree = fn : ('a -> 'b) -> 'a bintree -> 'b bintree *)
(* maps function over every node in a binary tree *)
```

```
- map_tree (fn x => x*2) int_tree;
val it = Node (Node (Leaf,4,Leaf),8,
               Node (Node (Leaf,2,Node (Leaf,10,Leaf)),12,
                     Node (Leaf,6,Leaf))) : int bintree

- map_tree (fn s => String.sub(s,0)) string_tree;
val it = Node (Node (Leaf,#"l",Leaf),#"g",
               Node (Node (Leaf,#"e",Leaf),#"a",
                     Node (Leaf,#"h",Leaf))) : char bintree
```

Sum-of-Product Datatypes in SML 14-17

Your turn: fold_tree




```
(* val fold_tree = fn : ('b * 'a * 'b -> 'b) -> 'b
   -> 'a bintree -> 'b *)
(* binary tree accumulation *)
```

```
- fold_tree (fn (lsum,v,rsum) => lsum + v + rsum) 0 int_tree;
val it = 21 : int

- fold_tree (fn (lstr,v,rstr) => lstr ^ v ^ rstr) " " string_tree;
val it = " like green eggs and ham " : string
```

Sum-of-Product Datatypes in SML 14-18

Binary Search Trees (BSTs) on integers



Sum-of-Product Datatypes in SML 14-19

Your turn: Binary Search Tree insertion

```
fun singleton v = Node(Leaf, v, Leaf)

(* val insert: 'a bintree -> 'a -> 'a bintree *)
```

```
fun listToTree xs =
  foldl (fn (x,t) => insert x t) Leaf xs
```

```
- val test_bst = listToTree [4,2,3,6,1,7,5];
val test_bst = Node (Node (Node (Node (Leaf,1,Leaf),
                                     2,
                                     Node (Leaf,3,Leaf)),
                             4,
                             Node (Node (Leaf,5,Leaf),
                                     6,
                                     Node (Leaf,7,Leaf))) : int bintree
```

Sum-of-Product Datatypes in SML 14-20

Your turn: Binary Search Tree membership

```
(val member: 'a -> 'a bintree -> bool *)
```

```
- member 3 test_bst;  
val it = true : bool  
  
- member 8 test_bst;  
val it = false : bool
```


Sum-of-Product Datatypes in SML 14-21

Balanced Trees (PS5 Problem 5)

BSTs are not guaranteed to be balanced.

But there are other tree data structures that do guarantee balance:
AVL trees, Red/Black trees, 2-3 trees, 2-3-4 trees.

In PS5 Problem 5 you will experiment with 2-3 trees.



Sum-of-Product Datatypes in SML 14-22