

Parameter Passing

Handout #39 *CS251 Lecture 32* *April 25, 2005*

Franklyn Turbak

Wellesley College

Parameter Passing, CS251 Spring '05 – p.1/2

Call-by-Value (CBV)

- In call-by-value (CBV), pass to a function the values resulting from evaluating the argument expressions.
- Example (HOFL substitution model):

```
((fun (x y) (* x x)) (+ 1 2) (* 3 4))  
⇒ ((fun (x y) (* x x)) 3 12) ; First eval args  
⇒ (* 3 3) ; Then substitute values  
⇒ 9 ; Then continue evaluation
```

Each argument expression is evaluated exactly once regardless of whether or not it is used in the body of the function.

- Alternative characterization: environments map names to (cells of) values.

Parameter Passing, CS251 Spring '05 – p.2/2

```

(* val eval: exp -> valu Env.env -> valu *)
let rec eval exp env =
  match exp with
  :
  | Var name ->
    (match Env.lookup name env with
     Some v -> v
     | None -> raise (EvalError("Unbound variable: " ^ name)))
  | Abs(fml,body) -> Fun(fml,body,env) (* make a closure *)
  | App(rator,rand) -> (* force left-to-right evaluation *)
    let fcn = (eval rator env) in
    let arg = (eval rand env) in apply fcn arg
  :

and apply fcn arg =
  match fcn with
  Fun(fml,body,senv) -> eval body (Env.bind fml arg senv)
  | _ -> raise (EvalError ("Non-function rator in application: "
                           ^ (valuToString fcn)))

```

Parameter Passing, CS251 Spring '05 – p.3/2

Call-by-Value: HOILIC Implementation

```

(* val eval: exp -> valu ref Env.env -> valu *)
let rec eval exp env =
  match exp with ...
  | Var name ->
    (match Env.lookup name env with
     Some cell -> ! cell
     | None -> raise (EvalError("Unbound variable: " ^ name)))
  | Assign(name,rhs) ->
    (match Env.lookup name env with
     Some cell -> let oldValu = (! cell)
                   and newValu = eval rhs env in
                   let _ = cell := newValu in oldValu
     | None -> raise (EvalError("Unbound variable: " ^ name)))
  | Abs(fml,body) -> Fun(fml,body,env) (* make a closure *)
  | App(rator,rand) -> (* force left-to-right evaluation *)
    let fcn = (eval rator env) in
    let arg = (eval rand env) in apply fcn arg

and apply fcn arg =
  match fcn with
  Fun(fml,body,senv) -> eval body (Env.bind fml (ref arg) senv)
  | _ -> raise (EvalError ...)

```

Parameter Passing, CS251 Spring '05 – p.4/2

Describe the evaluation of (testpp) in CBV HOILEC:

```
(def (test a b c)
  (seq (println "enter")
        (bind result (+ c (* b b))
                 (seq (println "exit")
                       result))))
```

```
(def (testpp)
  (test (println (+ 1 2))
        (println (+ 3 4))
        (println (+ 5 6))))
```

Parameter Passing, CS251 Spring '05 – p.5/2

Call-by-Value Languages

- Most modern languages are call-by-value (e.g. OCaml, Scheme, Java, C, Pascal value parameters).
- OCaml is like the HOILEC implementation: variables are bound directly to values, not cells holding values.
- Java, C, Pascal, Scheme are like the HOILIC implementation: each variable is bound to an implicit cell automatically dereferenced at each variable reference.

Parameter Passing, CS251 Spring '05 – p.6/2

- In call-by-name (CBN), pass to a function the unevaluated argument expressions. The argument is re-evaluated every time it is used in the body. It is never evaluated if it is never used.
- Example (HOFL substitution model):


```
((fun (x y) (* x x)) (+ 1 2) (* 3 4))
⇒ (* (+ 1 2) (+ 1 2)) ; Substitute unevaluated arg exprs
⇒ (* 3 3) ; Continue evaluation
⇒ 9
```
- Each argument expression is evaluated the number of times it is used in the function body. Better than call-by-value for arguments never used, but worse for arguments used more than once.
- Alternative characterization: environments map names to (cells of) thunks (i.e., unmemoized promises).
- ALGOL-60 was a call-by-name language.

Parameter Passing, CS251 Spring '05 – p.7/2

Call-by-Name: HOFL/HOILEC Implementation

```
(* val eval: exp -> (unit -> valu) Env.env -> valu *)
let rec eval exp env =
  match exp with ...
  | Var name ->
    (match Env.lookup name env with
     Some thunk -> thunk() (* dethunk *)
     | None -> raise (EvalError("Unbound variable: " ^ name)))
  | Seq(exp1,exp2) -> (* In CBN, seq is a kernel construct *)
    let _ = eval exp1 env in eval exp2 env
  | Abs(fml,body) -> Fun(fml,body,env) (* make a closure *)
  | App(rator,rand) -> (* force left-to-right evaluation *)
    let fcn = (eval rator env) in
    let arg = (fun () -> eval rand env) in
    apply fcn arg

and apply fcn arg =
  match fcn with
  Fun(fml,body,env) -> eval body (Env.bind fml arg env)
  | _ -> raise (EvalError ("Non-function rator in application: "
    ^ (valuToString fcn)))
```

Parameter Passing, CS251 Spring '05 – p.8/2

Describe the evaluation of `(testpp)` in CBN HOILEC:

```
(def (test a b c)
  (seq (println "enter")
        (bind result (+ c (* b b))
                (seq (println "exit")
                    result))))
```

```
(def (testpp)
  (test (println (+ 1 2))
        (println (+ 3 4))
        (println (+ 5 6))))
```

Parameter Passing, CS251 Spring '05 – p.9/2

Call-by-Lazy (CBL) a.k.a. Call-by-Need

- In call-by-lazy (CBL), pass to a function the unevaluated argument expressions. An argument is evaluated only the first time it is used in the body, and that value is used thereafter. It is never evaluated if it is never used.
- Example (HOFL/HOILEC substitution model):


```
((fun (x y) (* x x)) (+ 1 2) (* 3 4))
; Substitute (but share) unevaluated argument expressions
⇒ (* . .) ⇒ (* . .) ⇒ 9
      \ /          \ /
      (+ 1 2)          3
```
- Each argument expression is evaluated once if it is used in the function body, but zero times if it is never used. This is the best case scenario!
- Alternative characterization: environments map names to (cells of) memoized promises.
- The Haskell language uses call-by-lazy.

Parameter Passing, CS251 Spring '05 – p.10/2

```

(* val eval: exp -> valu Promise.promise Env.env -> valu *)
let rec eval exp env =
  match exp with ...
  | Var name ->
    (match Env.lookup name env with
     Some promise -> Promise.force promise
     | None -> raise (EvalError("Unbound variable: " ^ name)))
  | Seq(exp1,exp2) -> (* In CBL, seq is a kernel construct *)
    let _ = eval exp1 env in eval exp2 env
  | Abs(fml,body) -> Fun(fml,body,env) (* make a closure *)
  | App(rator,rand) -> (* force left-to-right evaluation *)
    let fcn = (eval rator env) in
    let arg = Promise.make (fun () -> eval rand env) in
    apply fcn arg

and apply fcn arg =
  match fcn with
  Fun(fml,body,env) -> eval body (Env.bind fml arg env)
  | _ -> raise (EvalError ("Non-function rator in application: "
    ^ (valuToString fcn)))

```

Parameter Passing, CS251 Spring '05 – p.11/2

Call-by-Lazy Example

Describe the evaluation of (testpp) in CBL HOILEC:

```

(def (test a b c)
  (seq (println "enter")
       (bind result (+ c (* b b))
                 (seq (println "exit")
                      result))))

(def (testpp)
  (test (println (+ 1 2))
        (println (+ 3 4))
        (println (+ 5 6))))

```

Parameter Passing, CS251 Spring '05 – p.12/2

- In a purely functional language, evaluating expression E under call-by-name and call-by-lazy always gives the same result.
- In a purely functional language, if E evaluates to values V_V , V_N , and V_L call-by-value, call-by-name, and call-by-lazy (respectively), then V_V , V_N , and V_L must be the same value.
- However, call-by-name/need will sometimes return values in cases where call-by-value fails to do so (because of errors or infinite loops).
E.g.:

```
((fun (x y) (* x x)) (+ 1 2) (/ 3 0))
((fun (x y) (* x x)) (+ 1 2) (loop))
; Suppose (loop) loops infinitely
```

- In an imperative language, all bets are off. That is, for some expressions, each mechanism can return a completely different value.

Parameter Passing, CS251 Spring '05 – p.13/2

Call-by-Reference (CBR)

In call-by-reference (CBR), all argument expressions are evaluated as in CBV. But pass to a function the reference cell of any parameter that is a variable. (Create a new reference cell for parameters that are not variables).

;; CBR example in HOILIC

```
(bind a 0
  (bind inc (fun (x)
              (seq (<- x (+ x 1))
                   a)))
  (list a ; In both CBV and CBR, returns 0
        (inc a) ; CBV returns 0; CBR returns 1
        (inc a))) ; CBV returns 0; CBR, returns 2
```

Parameter Passing, CS251 Spring '05 – p.14/2

```

(* val eval : exp -> valu ref Env.env -> valu *)
let rec eval exp env = match exp with
  App(rator,rand) ->
    let fcn = (eval rator env) in
    let arg = (eval rand env) in apply fcn arg
  | ... (* all other clauses same as for CBV *)

(* val leval : exp -> valu ref Env.env -> valu ref *)
and leval exp env = match exp with (* Evaluate "left" value *)
  | Var name -> (match Env.lookup name env with
    Some cell -> cell (* Return cell, not contents *)
    | None -> raise (EvalError("Unbound variable: " ^ name)))
  | If(tst,thn,els) -> (match eval tst env with
    Bool true -> leval thn env
    | Bool false -> leval els env
    | v -> raise (EvalError ...))
  | _ -> ref (eval exp env) (* else create fresh cell for value *)

(* val apply: fcn -> valu ref -> valu *)
and apply fcn argref = match fcn with
  Fun(fml,body,env) -> eval body (Env.bind fml argref env)
  | _ -> raise (EvalError ...)

```

Parameter Passing, CS251 Spring '05 – p.15/2

Call-by-Reference in Pascal

Pascal supports both call-by-value and call-by-reference.

Call-by-reference parameters are distinguished with a `var` keyword in parameter declarations.

```

program ParamTest (input,output);
  var a, b: integer;
  procedure paramTest (x:integer, var y:integer);
    begin
      x := x + y;
      y := x * y;
    end;
  begin
    a := 3;
    b := 4;
    paramTest(a,b);
    writeln('a=', a); {a is still 3}
    writeln('b=', b); {b is now 28}
  end;
end.

```

Parameter Passing, CS251 Spring '05 – p.16/2


```

program TestSwap;
  procedure swap (var x : int, var y : int);
    begin
      var temp:integer := x;
      x := y;
      y := temp;
    end;
  begin
    var a:integer := 1;
    var b:integer := 2;
    swap(a,b); {a now contains 2 and b contains 1}
    {Can also call swap on array slots:
     e.g. swap(c[i],d[j]).}
  end;
end.

```

Parameter Passing, CS251 Spring '05 – p.17/2

Simulating Call-by-reference in C

C is call-by-value, but has pointer operations for simulating call-by-reference:

- The *address-of operator* (&) returns location of (i.e. pointer to) a variable.
- The *dereference operator* (*) returns contents of a pointed-at variable.

Encoding `paramTest` example in C:

```

void paramTest (int x, int* y) {
  x = x + *y;
  *y = x * *y;}

int main () {
  int a = 3;
  int b = 4;
  paramTest(a,&b);
  printf("a=%d; b=%d\n", a, b);}

[fturbak@jaguar c] gcc -o paramtest paramtest.c
[fturbak@jaguar c] paramtest
a=3; b=28

```

Parameter Passing, CS251 Spring '05 – p.18/2

```

void printab (int x, int y) { printf("a=%d; b=%d\n", x, y);}

void swap (int* x, int* y) {
    int temp;
    printf("x=%u; *x=%d; y=%u; *y=%d\n",x,*x,y,*y); // %u for unsigned int
    temp = *x; *x = *y; *y = temp;
    printf("x=%u; *x=%d; y=%u; *y=%d\n",x,*x,y,*y);}

int main () {
    int a = 1;
    int b = 2;
    printab(a,b);
    swap(&a,&b); // Can also swap array slots: e.g. swap(&c[i], &d[j])
    printab(a,b);}

[fturbak@jaguar c] gcc -o swap swap.c; ./swap
a=1; b=2
x=3221223268; *x=1; y=3221223264; *y=2
x=3221223268; *x=2; y=3221223264; *y=1
a=2; b=1

```

Parameter Passing, CS251 Spring '05 – p.19/2

Call-by-reference in C++

C++ supports call-by-reference parameters:

```

void swap (int &x, int &y) {
    int temp = x;
    x = y;
    y = temp;}

int main () {
    int a = 1;
    int b = 2;
    swap(a,b); // a now contains 2 and b contains 1
    // Can also swap array slots: e.g. swap(c[i], d[j])}

```

Parameter Passing, CS251 Spring '05 – p.20/2

In OCaml, call-by-reference simulated by passing explicit cells (references):

```
fun swap (x, y) =  
  temp = ! x;  
  x := ! y;  
  x := temp
```

```
let a = ref 3  
let b = ref 4  
let _ = swap(a, b)
```

The same trick can be pulled in Scheme and Java. Note that there is no way to access the implicit cells that variables are bound to in Scheme and Java, so it is impossible to write a swap function on the implicit cells. E.g., if `a` and `b` are Java variables, there is no `swap` function such that `swap(a, b)` swaps the values of `a` and `b`.