





# Undecidable Problems About Languages




# Today's adventures

---





- Undecidability
- New proof technique/tool: reduction proofs!
- Prove undecidability for `HALT_TM`, `E_TM`, `EQ_TM`, `REGULAR_TM`

Weekly tip: Reflect on “be” versus “do”



# Reducibility







# Clique and Independent Set

---

CLIQUE =  $\{ \langle G, k \rangle \mid G \text{ is a graph with a } k\text{-clique} \}$






INDEPENDENT =  $\{ \langle G, k \rangle \mid G \text{ is a graph containing an independent set of size } k \}$



# CLIQUE reduces to INDEPENDENT

---






# Certified Impossible

---

**Theorem.**  $A_{\text{TM}} = \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ accepts } w \}$  is undecidable.

**Definition.**  $\text{HALT}_{\text{TM}} = \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on input } w \}$




# The Halting Problem (Again!)

---

**Theorem.**  $HALT_{TM}$  is undecidable.

**Proof Idea.** We know  $A_{TM}$  is undecidable. We need to reduce one of  $HALT_{TM}$  or  $A_{TM}$  to the other.

Which way to go?




$HALT_{TM}$  is undecidable

---

**Proof.**

Suppose  $R$  decides  $HALT_{TM}$ . Define






# Does $M$ Accept Anything at All?

---

**Definition.**  $E_{\text{TM}} = \{ \langle M \rangle \mid M \text{ is a TM and } L(M) = \emptyset \}$

**Theorem.**  $E_{\text{TM}}$  is undecidable.





$$E_{\text{TM}} = \{ \langle M \rangle \mid M \text{ is a TM \& } L(M) = \emptyset \}$$


---

**Proof.**

Given an input  $\langle M, w \rangle$  we construct a machine  $M_w$  as follows:





# With Power Comes Uncertainty

---

$M$  accepts  $w$


$L(M) = \emptyset$

$L(M_1) = L(M_2)$

Turing machines

Pushdown  
machines


Finite machines



# It's Even Worse Than You Thought

---

**Rice's Theorem.**    *Any nontrivial property of the languages recognized by Turing machines is undecidable.*




# For Example

---

**Definition.**  $REGULAR_{TM} = \{ \langle M \rangle \mid M \text{ is a TM and } L(M) \text{ is regular} \}.$

**Theorem.**  $REGULAR_{TM}$  is undecidable.




$REGULAR_{TM}$  is undecidable


---

**Proof.**

For a contradiction, let  $R$  be a TM that decides  $REGULAR_{TM}$ . Define

$S =$  “On input  $\langle M, w \rangle$ :





# Problems

---

- Let  $EQ_{TM} = \{ \langle M_1, M_2 \rangle \mid M_1 \text{ and } M_2 \text{ are TMs and } L(M_1) = L(M_2) \}$ . Show that  $EQ_{TM}$  is undecidable by reducing  $E_{TM}$  to  $EQ_{TM}$ .
- Consider the problem of determining whether a two-tape TM ever writes a nonblank symbol on its second tape when run on input  $w$ . Formulate this problem as a language and show that it is undecidable. (Hint: create an intermediary TM  $T$  that writes a nonblank symbol on its second tape iff  $M$  accepts  $w$ .)