

# CS 240 Laboratory 7

## Pointers and Introduction to gdb

### Pointers

A pointer is a variable that contains the address of another variable.

Since a pointer contains the address of an object, it is possible to access the object “indirectly” through the pointer. For example,

```
int x;  
int* px;  
px = &x;
```

means `px` contains the address of `x`, or “points” to `x`.

Similarly,

```
int y = *px;
```

means that `y` gets the value stored at the address in `px` (the value `px` “points” to).

You can do dereference more than once with the use of multiple operators:

```
char** commandA;
```

means `commandA` is a *pointer* to an array of *pointers to chars* (which we can think of as strings).

Another way to say this is that it references an *address* to an array of *addresses*.

Assuming that space in memory has been allocated, draw a memory diagram showing the result of executing the following statements:

```
commandA[0] = "emacs";  
commandA[1] = "strings.c";  
commandA[2] = NULL;
```

## **Pointer Arithmetic**

If  $p$  is a pointer, then  $p++$  increments  $p$  to point to the next element of whatever kind of object  $p$  points to. So, the actual number by which  $p$  gets increments is a multiple of the size in bytes of the object pointed to.

```
int *p;  
p++;
```

results in  $p$  being incremented by the size of an integer in bytes on the particular machine on which the operation is performed.

If the word size is 32 bits,  $p$  is incremented by 4.

If the word size is 64 bits,  $p$  is incremented by 8.

## Important Data Types

The result of subtracting two pointers in C is always an integer, but the precise data type varies from C compiler to C compiler. Likewise, the data type of the result of *sizeof* also varies between compilers.

### **ptrdiff\_t**

This is the signed integer type of the result of subtracting two pointers. For example, with the declaration:

```
Char* p
```

the expression `p2 - p1` is of type `ptrdiff_t`. This will probably be one of the standard signed integer types (short int, int or long int), but might be a nonstandard type that exists only for this purpose.

### Data Type: **size\_t**

This is an unsigned integer type used to represent the sizes of objects. The result of the `sizeof` operator is of this type.

**Usage Note:** *size\_t* is the preferred way to declare any arguments or variables that hold the size of an object.

## Memory Allocation

# GNU Debugger (gdb)

## Tutorials and manuals:

<http://wellesleycs240.bitbucket.org/tools.html>

## Commands

Can be shortened to a single letter, or repeated by entering <return> at the prompt):

- Compile C program with **-g** option to create debugging information
- Run the program under **gdb**

```
$ gdb testprog
```

```
(gdb) run
```

- Set breakpoints

```
(gdb) break main
```

- Step/next statement by statement through your program

```
(gdb) step
```

```
(gdb) next
```

```
(gdb) cont           -- continue execution
```

- Display/print code or values of variables and arguments

**(gdb) list**

**(gdb) print x**

**(gdb) info locals**

**(gdb) info args**

- **(gdb) quit** or **Ctrl-d** -- to exit.

- To find a bug:

1. Set breakpoints at the start of every function

2. Restart the program and step line-by-line until you locate the problem exactly.

3. If program is stuck (infinite loop) **Ctrl-c** terminates the action of any gdb command that is in progress and returns to the gdb prompt.

- Execute statements/expressions during execution to tweak program execution state

**(gdb) set var i = 2**

- Display/print binary and hexadecimal representation of variables and arguments

**(gdb) print /x result** -- uses hex representation

**(gdb) print /t result** -- uses binary representation

