

**Assignment for Lab 11**  
**Data Structure Representations**  
*Computer Science 240*

In lab this week, you will write some assembly language programs to study how data structures are stored in memory. To investigate this concept, it is useful to write some X86 assembly code directly (rather than producing it by compiling C code, as we have been doing up to now).

### Assembly Directives

When you create X86 code directly, you will include *assembly directives*, which begin with a dot and indicate structural information useful to the assembler, linker, or debugger, but are not in and of themselves assembly instructions. For example, we use:

```
.globl main
```

to indicate that the label *main* is a global symbol that can be accessed by other code modules.

We state what part of memory to store code or data, and also declare and initialize all variables and strings, using the following directives:

```
.text .data, .quad, and .string
```

To see a list of possible directives, visit: <http://tigcc.ticalc.org/doc/gnuasm.html#SEC67>

We can also use variable names directly in X86 to reference memory locations.

Below is an example of a simple C program, and on the right is an X86 program that performs the equivalent task. Read carefully to correlate the C code to the X86:

**simple.c:** (C code)

```
#include <stdio.h>
```

```
long total = 0;
```

**simple.s:** (X86 code)

```
.data //use the data segment of memory for  
      //global variables and literal strings
```

```
total: .quad 0           //8 bytes with initial value 0
```

```
fstr1: .string "Sum = %d\n" //formatting string for printf
```

```
fstr2: .string "Total = %d\n" //formatting string for printf
```

```

                                .text          //use the text segment of memory for code

                                .globl main    //the main method must be
                                                //declared as global

int sum(int x,int y) {          sum:
    int t = x + y;              lea (%rsi,%rdi,1),%eax //adds x + y, stores result in %eax

total +=t;                       add %eax,total        //variable name is used
                                                // to reference address in memory

return t;                          ret
}

int main() {                    main:
    int x = 2;                   mov $0x3,%esi
    int y = 3;                   mov $0x2,%edi

    printf("Sum = %d\n",sum(x,y)); call sum              //returns value in %eax

                                                mov %eax,%esi //sets up parameters and calls printf
                                                mov $fstr1,%edi
                                                mov $0x0,%eax
                                                call printf

    printf("Total = %d\n",total); mov $total,%esi //sets up parameters and calls printf
                                                mov $fstr2,%edi
                                                mov $0x0,%eax
                                                call printf

    return 0;                     mov $0x0,%eax
}
ret

```

1. Using the previous program as a guide, write an X86 program which implements the following C program (do NOT use the computer to compile the C program and produce the X86 code: write it from scratch).

```

#include <stdio.h>
int z;
int square(int n) {
    return n*n;
}
int main() {
    int x = square(3);
    int y = square(4);
    z = x + y;
    printf("Calculation produces %d\n",z);
    return 0;
}

```