**CS 251** Fall 2019
Principles of Programming Languages
Ben Wood

WELLESLEY

# Datatypes, Patterns, and Parametric Polymorphism



## Topics

- Tuples and records
- Positional vs. nominal
- **Datatypes**
- **Pattern matching**
- **Parametric polymorphic types** (generics)
- Lists and options
- Equality types



## Tuples

Syntax: `(e1, …, en)`

Evaluation:

1. Evaluate e1 to v1, …, and en to vn.
2. The result is (v1, …, vn)

Type checking:

If e1 has type t1, …, and en has type tn,
then the pair expression has type ta * … * tn



## Tuple bindings

Syntax: `val (x1, x2) = e`

Type checking:

If `e` has type `t1 * t2`,
then `#1 e` has type `t1` and `#2 e` has type `t2`

Evaluation:

1. Evaluate `e` to a pair of values `(v1, v2)` in the current dynamic environment
2. Extend the current dynamic environment by binding `x1` to `v1` and `x2` to `v2`.

*Poor style.*

# Tuple accessors

Syntax: `#1 e` `#2 e`

**Type checking:**

If `e` has type `t1 * t2`,
then `#1 e` has type `t1` and `#2 e` has type `t2`

**Evaluation:**

1. Evaluate `e` to a pair of values `v1` and `v2` in the current dynamic environment
2. The result `v1` if using `#1`; `v2` if using `#2`



# Examples

```
fun swap (pr : int*bool) =
  let val (x,y) = pr in (y,x) end

fun sum_two_pairs (pr1 : int*int, pr2 : int*int) =
  let val (x1,y1) = pr1
      val (x2,y2) = pr2
  in x1 + y1 + x2 + y2 end

fun div_mod (x : int, y : int) =
  (x div y, x mod y)

fun sort_pair (pr : int*int) =
  let val (x,y) = pr
  in
    if x < y then pr else (y,x)
  end
```



# Records

*Record values* have fields (any name) holding values

`{f1 = v1, …, fn = vn}`

*Record types* have fields (any name) holding types

`{f1 : t1, …, fn : tn}`

Order of fields in a record value or type never matters

Building records:

`{f1 = e1, …, fn = en}`

Accessing components:

`#myfieldname e`

(Evaluation rules and type-checking as expected)



# Example

`{name = "Wendy", id = 41123 - 12}`

Has type `{id : int, name : string}`

Evaluates to `{id = 41111, name = "Wendy"}`

If an expression, e.g. variable `x`, has this type, then get fields with:

`#id x` `#name x`

No record type **declarations!**

- The same program could also make a `{id=true,ego=false}` of type `{id:bool,ego:bool}`

Design Choice

# By position vs. by name

*(structural/positional)* *(nominal)*

`(4,7,9)` `{f=4,g=7,h=9}`

Common syntax decision

Common hybrid: function/method arguments



# Tuples are sugar

`(e1,…,en)`
desugars to
`{1=e1,…,n=en}`

`t1*…*tn`
desugars to
`{1:t1,…,n:tn}`

Records with contiguous fields 1…n printed like tuples
Can write `{1=4,2=7,3=9}`, bad style



# Lists

Racket: **`(cons 1 (cons 2 (cons 3 null)))`**

ML has a "no value" value written **`()`**, pronounced "unit," with type **`unit`**

What is the type of: **`(1, (2, (3, ())))`**

What is the type of: **`(1, (2, (3, (4, ()))))`**

Why is this a problem?



# How to build bigger data types

Data type building blocks in *any* language

- Product types ("Each of"):
  Value contains *values of each of* `t1 t2 … tn`
  Value contains *a* `t1` *and* a `t2` *and* … *and* a `tn`
- Sum types ("One of"):
  Value contains *values of one of* `t1 t2 … tn`
  Value is `t1` *xor* a `t2` *xor* … *xor* a `tn`
- Recursive types ("Self reference"):
  A `t` value can refer to other `t` values

# Datatype bindings

```
datatype mytype = TwoInts of int * int
                | Str of string
                | Pizza
```

Algebraic Data Type

- Adds new type `mytype` to environment
- Adds *constructors* to environment: `TwoInts`, `Str`, `Pizza`
- Constructor: function that makes values of new type (or is a value of new type):
  - `TwoInts : int * int -> mytype`
  - `Str : string -> mytype`
  - `Pizza : mytype`



# Datatypes: constructing values

```
datatype mytype = TwoInts of int * int
                | Str of string
                | Pizza
```

- Values of type `mytype` produced by *one of* the constructors
- Value contains:
  - Tag: which constructor (*e.g.*, `TwoInts`)
  - Carried value (*e.g.*, `(7,9)`)
- Examples:
  - `TwoInts (3+4,5+4)` evaluates to `TwoInts (7,9)`
  - `Str if true then "hi" else "bye"` evaluates to `Str "hi"`
  - `Pizza` is a value



# Datatypes: using values

1. Check what *variant* it is (what constructor made it)
2. Extract carried *data* (if that variant has any)

ML *could* create functions to get parts of datatype values

- Like to *pair?* or *cdr* in Racket
- Instead it does something **much** better…



# Pattern matching


***Case expression*** and ***pattern-matching***

```
fun f x = (* f has type mytype -> int *)
    case x of
        Pizza => 3
      | TwoInts(i1,i2) => i1+i2
      | Str s => String.size s
```

All-in-one:

- Multi-branch conditional, picks branch based on variant.
- Extracts data and binds to branch-local variables.
- Type-check: all branches must have same type.

- Gets even better later.

# Pattern matching

Syntax:

```
case e0 of
     p1 => e1
   | p2 => e2
     …
   | pn => en
```

- (For now), each pattern ***pi*** is:
  - a constructor name followed by the right number of variables:
  - **C** or **D x** or **E (x,y)** or …
- Patterns are not expressions.
  - We do not evaluate them.
  - We match e0 against their structure.
- Precise type-checking/evaluation rules later…



# Pattern matching rocks.

1. Cannot forget a case
   (inexhaustive pattern-match warning)
2. Cannot duplicate a case
   (redundant pattern type-checking error)
3. Cannot forget to test the variant correctly
   and get an error (`(car null)` in Racket)
4. It's much more general.
   Supports elegant, concise code.



# Useful examples

Enumerations, carrying other data

```
datatype suit = Club | Diamond | Heart | Spade
datatype card_value = Jack | Queen | King
                    | Ace | Num of int
```

Alternate ways of identifying real-world things/people

```
datatype id = StudentNum of int
            | Name of string
                    * (string option)
                    * string
```



# Lists!

A list is either:

- The empty list; or
- A pair of a list element and a list that holds the rest of the list.

```
datatype mylist = Empty
                | Cons of int * mylist
```

datatypes can be recursive

```
val some_ints = Cons (1, Cons (2, Cons (3, Empty)))
```

# Accessing Lists

```
val some_ints = Cons (1, Cons (2, Cons (3, Empty)))
```

```
fun length (xs : mylist) =
  case xs of
      Empty => 0
    | Cons (x, xs') => 1 + length xs'
```

```
fun sum (xs : mylist) =
  case xs of
      Empty => 0
    | Cons (x, xs') => x + sum xs'
```



# Syntactic sugar for lists: build

The empty list is a value: `[ ]`

A list of expressions/values is an expression/value:

`[e1,e2,…,en]` `[v1,v2,…,vn]`

If `e1` evaluates to `v`
and `e2` evaluates to a list `[v1,…,vn]`,
then `e1::e2` evaluates to `[v,v1,…,vn]`



# Syntactic sugar for lists: access

```
val some_ints = [1,2,3]
```

note the space between `int` and `list`

```
fun length (xs : int list) =
  case xs of
      [] => 0
    | x::xs' => 1 + length xs'
```

```
fun sum (xs : int list) =
  case xs of
      [] => 0
    | x::xs' => x + sum xs'
```



# Type-checking list operations

For any type `t`, type `t list` describes lists where all elements have type `t`

```
int list    bool list     int list list
(int * int) list    (int list * int) list
```

`[] : t list` list for *any* type `t`

SML uses type `'a list` to indicate this (“quote a” or “alpha”)

`e1::e2 : t list` if and only if:

- `e1 : t` and
- `e2 : t list`

**More on 'a soon!** *(Nothing to do with 'a in Racket.)*

# Example list functions

(types?)

```
fun countdown (x : int) =
  if x=0
  then []
  else x :: countdown (x-1)

fun append (xs : int list, ys : int list) =
  case xs of
      [] => ys
    | x::xs' => x :: append (xs', ys)

fun rev (xs : int list) =
  let fun revtail (acc : int list, xs : int list) =
        case xs of
            [] => acc
          | x::xs' => revtail (x :: acc, xs')
  in
    revtail ([], xs)
  end
```



(type?)

# Example higher-order list functions

```
fun map (f : int -> int, xs : int list) =
  case xs of
      [] => []
    | x::xs' => f x :: map (f, xs')
```

- These examples only work on lists of ints.
- Should be more general: work on any list
  - and any function for map…



# Polymorphic types + type inference

The identity function: `fun id (x : int) = x`

`val id : int -> int`

Omit the type: `fun id x = x`

`val id : 'a -> 'a`

**General!**

- `'a` is a ***polymorphic type variable*** stands in for *any type*
- *"id takes an argument of any type and returns a result of that same type."*



# Polymorphic types + type inference

```
fun swap pair =
    let val (x,y) = pair in (y,x) end
val swap : ('a * 'b) -> ('b * 'a)
```

Works on ***any*** type of pair!

```
val pair = swap (4,"hello")
```

`('a * 'b)` is ***more general than*** `(int * string)`.

Here, `int` ***instantiates*** `'a` and `string` ***instantiates*** `'b`.

# Polymorphic datatypes

Lists that can hold elements of any one type.

```
datatype 'a mylist = Empty
                   | Cons of 'a * 'a mylist
```

A list of "alphas" is either:

- the empty list; or
- a pair of an "alpha" and a list of "alphas"

```
datatype 'a list = []
                 | :: of 'a * 'a list
```

The type **`int list`** is an *instantiation* of the type `'a list`, where the type variable `'a` is *instantiated* with `int`.



# Polymorphic list functions

(types?)

```
fun append (xs, ys) =
  case xs of
      [] => ys
    | x::xs' => x :: append (xs', ys)

fun rev (xs) =
  let fun revtail (acc : int list, xs : int list) =
        case xs of
            [] => acc
          | x::xs' => revtail (x :: acc, xs')
  in revtail [] xs end

fun map (f, xs) =
  case xs of
      [] => []
    | x::xs' => f x :: map (f, xs')
```



# Polymorphic list functions

(type?)

```
fun map (f, xs) =
  case xs of
      [] => []
    | x::xs' => f x :: map (f, xs')
```

- Type inference system chooses most general type.
- Polymorphic types show up commonly with higher-order functions.
- Polymorphic function types often give you a good idea of what the function does.



# Exceptions

An exception binding introduces a new kind of exception

```
exception MyFirstException
exception MySecondException of int * int
```

The `raise` primitive raises (a.k.a. throws) an exception

```
raise MyFirstException
raise (MySecondException (7,9))
```

A handle expression can handle (a.k.a. catch) an exception

- If doesn't match, exception continues to propagate

```
e1 handle MyFirstException => e2
e3 handle MyFirstException => e4
     | MySecondException (x,y) => e5
```

# Actually...

Exceptions are a lot like datatype constructors...

- Declaring an exception adds a constructor for type `exn`
- Can pass values of `exn` anywhere (e.g., function arguments)
  - Not too common to do this but can be useful
- `handle` can have multiple branches with patterns for type `exn`, just like a `case` expression.
- See examples in exnopt.sml



# Options

```
datatype 'a option = NONE | SOME of 'a
```

`t option` is a type for any type `t`

Building:
- `NONE` has type `'a option` (much like `[]` has type `'a list`)
- `SOME e` has type `t option` if `e` has type `t` (much like `e::[]`)

Accessing:
- Pattern matching with case expression

Good style for functions that don't always have a meaningful result.
See examples in exnopt.sml



# Parametric Polymorphism and the power of what you cannot do.

Type 'a means "some type, but don't know what type"

*What can a function of type* `'a list -> int` *do?*

```
fun f (xs : 'a list) : int = ...
```

`'a -> 'a` ?

```
fun g (x : 'a) : 'a = ...
```



# Equality Types

Special case of what should be more general feature...

So if we cannot inspect values of type 'a in any way, how do we write a general `contains` function?

```
fun contains (xs : 'a list, x : 'a) : bool = ...
```

***eqtypes (equality types):***
Special category of types that support comparison.
Accompanying eqtype variables with double quotes

Mostly accurate:
`= : (''a * ''a) -> bool`

```
fun contains (xs : ''a list, x : ''a) : bool = ...
```